

## How to Optimize the Performance of Motion Platforms with ACS

UNIQUE ACS MOTION CONTROL FEATURES ENHANCE POSSIBILITIES IN INDUSTRIAL AUTOMATION

# Different Markets and Applications and Their Specific Requirements

		Semiconductor Inspection, Metrology, Lithography (Front End)	Semiconductor Packaging (Back End)	Flat Panel Display Inspection & Metrology	Electronics Assembly (PCB SMT / Automated Programming)	Electronics Dispensing	Laser Cutting	Laser Microprocessing	Digital / Inkjet Printing	Genome Sequencing	Medical Scanners	Additive Manufacturing / 3D Printing	Fiber Optics Packaging & Alignment
General Features	Multiple drive types in one application	•	•	•	•	•	•	•	•	•	•	•	•
	Multiple sensor types in one application	•	•	•	•	•	•	•	•	•	•	•	•
	Modular volume production	•	•	•	•	•	•	•	•	•	•	•	•
Safety / Reliability	Functional safety STO inputs	•	•	•	•	•	•	•	•	•	•	•	•
	Network redundancy		•		•								
Communication with Host	EtherCAT communication to PLC	•	•		•	•	•	•	•			•	•
	EthernetIP communication to PLC	•	•		•	•	•	•	•			•	•
	Controller processes NC files / G-Code					•	•	•				•	
	CAD to motion					•	•	•				•	
	CNC style user interface					•	•	•				•	
Controller	3rd party EtherCAT drive / IO support	•	•	•	•	•	•	•	•	•	•	•	•
Drivers	Dual loop	•	•	•	•	•	•	•	•	•	•	•	•
	Flexible encoder support (AqB, optical sin/cos, laser / interferometer sin/cos, absolute)	•	•	•	•	•	•	•	•	•	•	•	•
	Highly dynamic motion: high acceleration, high speed	•	•	•	•		•	•	•	•		•	
	Universal motor support (stepper, voice coil / DC brush servo, BLDC servo)	•	•	•	•	•	•	•	•	•	•	•	•
	High power	•	•	•	•	•	•		•		•	•	
Motion / Trajectory	Trajectories for small features / motions	•	•	•	•		•	•	•	•		•	
	Gantry control	•	•	•	•	•	•	•	•			•	
	Implement complex motion-time events and sequences	•	•	•	•	•	•	•	•	•	•	•	•
	Constant velocity motion smoothness	•		•					•				
	Demanding stand-still jitter	•		•					•	•			
Synchronization	Event (laser, camera, etc.) synchronization with motion - triggering or on/off control	•		•	•	•	•	•	•			•	
	Multi-axis coordinated motion (circular / spherical / 5-axis)				•	•	•	•				•	
	Multi-axis coordinated PTP motion	•	•	•	•	•	•	•	•	•	•	•	•
Easy Tuning	Demanding accuracy specifications	•	•	•	•	•	•	•	•	•	•	•	•
	High performance: load changes		•		•						•		
Vertical or Bridge Axis	High throughput laser processing - Galvo / stage motion sync	•		•					•	•			
	Autofocus height control	•	•	•			•	•	•			•	•

# How ACS Features Optimize an Automation Process

## General Features

- Powerful and high bandwidth EtherCAT motion system network
- Control multiple drive, feedback and sensor types in one platform
- Expandable, modular and flexible  
[Flexible Configuration](#)

## Communication with Host via PLC or PC

- Communicate with sophisticated Host PC User Interface applications using powerful [API libraries](#)
- Communicate with standalone and PC based PLCs/PACs via EtherCAT, EthernetIP, ModbusTCP
- EtherCAT PLC to [SPiiPlusES](#): allows CiA402/DS402 compatible, synchronous, asynchronous operation, high performance motion control network
- CAD to motion: define and plan trajectory by [G-Code](#), use [Look Ahead](#) for low error motion, develop machine with [SPiiPlusSPC](#)
- CNC HMI style user interface [SPiiPlusSMC](#) provides flexible CNC [G-Code](#) control capabilities

## Safety / Reliability

- Certified machine functional safety [STO inputs](#)
- [NetworkBoost](#) for safe operation even during network device failures
- CE and UL certified products



## Drives


- [Universal motor support](#)
- Supporting many common industrial encoder types (AqB, Optical / Laser SinCos, absolute...)
- Wide power range
- Industry leading update rates and control algorithms (dual loop with on the fly [Encoder Switching](#), [Multiple Encoder Channels per Axis](#), [ServoBoost](#))

## Controllers

- Flexible and open EtherCAT based network
- Up to 64 axes and thousands of I / Os
- Implement complex motion-time events and sequences using [ACSPL+](#) language and [PEG](#) and [LCM](#) outputs

### Easy Tuning

- Install, configure, and tune axes quickly with an intuitive user interface
- Automated adaption to load changes [ServoBoost](#)



### Vertical or Bridge Axis

- Synchronized autofocus height control
- Synchronization of galvo scanner and stage motion, [XLScan System](#)
- Direct laser control and triggering during motion [LCM](#)

### Motion / Trajectory

- Miniature features require small position errors at high speed [4/5 kHz MPU Cycle](#)
- Trajectory definition by [G-Code](#)
- Vibration cancelling [Input Shaping](#)
- Settling / standstill with minimal following error [NanoPWM](#)
- Highly dynamic motion [ServoBoost](#)
- Easy configuration, motors mapped to logical axes [Gantry Algorithm](#)
- 2D / 3D coordinated motion [Corner Processing](#), [Error Mapping](#)

### Synchronization

- High absolute accuracy, position stability
- Multi-axis coordinated motion (circular, spherical, 5-axis) with minimum position errors [Look Ahead](#)
- Smooth motion at constant velocity [ServoBoost](#), [Encoder Switching](#)
- Event trigger for time, position, with high resolution [PEG outputs](#), [Laser Synchronization \(LCM\)](#)

# Details of ACS Features and Options

	Name	Function
Standard features of ACS systems (system = controller + drives)	ACSPL+ Programming	ACSPL+ is a motion control oriented multi-threading high level language with up to 64 threads running simultaneously. It simplifies implementation of highly complex motion-time events and sequences with accurate positioning and timing.
	API libraries	Application programming interface is a set of libraries and tools for building software applications. For example .net for Windows applications.
	Corner Processing	Increase throughput by rounding sharp corners.
	Error Mapping	Bring accuracy to level of repeatability. Requires external equipment for measuring.
	Gantry Algorithm	Much simpler tuning and configuration of gantry systems, with improved performance.
	Look Ahead	Avoids excessive accelerations and shocks to the system while maintaining high throughput and accuracy.
	Multiple Encoder Channels Per Axis	For flexible dual loop assignment. Free of charge but should be ordered in advance, not available for all products.
	PEG Outputs	For triggering external devices or data collection at specific encoder positions.
	Universal Motor Support	Each drive supports stepper motors, voice coils and linear motors as well as brush and brushless DC motors.
Options to be ordered at extra charge	4/5 kHz MPU Cycle	Higher frequency profile generation allows smoother accelerations and corner path.
	Encoder Switching	Robust handling of multiple feedbacks, allows use of very high resolution encoder only in limited process window, and lower resolution encoder over entire travel range. Custom, application specific development.
	Flexible Configuration	User can define subsystems of the network which can be operated independently e.g. during setup and production.
	G-Code	Mandatory for CNC applications, common for many Additive Manufacturing applications.
	Input Shaping	Avoid exciting resonance.
	NetworkBoost*	Enables redundancy in case of network cable / node failures which can be more likely with remotely mounted drives. Results: <ul style="list-style-type: none"> <li>• Safe operation during single failure</li> <li>• Indication of the situation</li> <li>• Recoverable during operation</li> </ul>
	ServoBoost**	Enhances servo performance, keeping actual motion closer to ideal. It provides automatic adaptation to large changes in load and system parameters and automatic compensation of disturbances, resonances, axes interaction, cogging and more. Results: <ul style="list-style-type: none"> <li>• Faster settling</li> <li>• Better stability</li> <li>• Lower jitter</li> <li>• Better constant velocity</li> </ul>
	STO Inputs **	Achieve certified machine safety (Safe Torque Off).
Products which extend the functionality of ACS systems	LCM for laser synchronization	A hardware module that coordinates the motion with the laser operation.
	NanoPWM line	All NanoPWM drives feature the DRBoost which results in unprecedented current control dynamic range of above 100 db.
	SPiiPlusES	This controller is a SPiiPlusEC controller with an additional external EtherCAT bridge which allows any ACS solution to act as high performance motion control subsystem under other EtherCAT master such as TwinCAT.
	SPiiPlusSMC	UI / HMI platform (software) for CNC control based machines - can save machine developer many hours / weeks of effort (vs. 'building from scratch').
	SPiiPlusSPC	Graphical UI platform (software) for laser processing / additive manufacturing machines - can save machine developer many hours/weeks of effort (vs. 'building from scratch').
	XLScan System	Extends a laser scan system's working filed by simultaneously controlling and moving a scan head and an XY-stage. Special system, must be ordered from ACS and Scanlab.

\* not available for all controllers

\*\* not available for all drives



## Headquarters

### GERMANY

**Physik Instrumente (PI) GmbH & Co. KG**  
 Auf der Roemerstrasse 1  
 76228 Karlsruhe  
 Phone +49 721 4846-0  
 Fax +49 721 4846-1019  
 info@pi.ws  
 www.pi.ws

**PI miCos GmbH**  
 Freiburger Strasse 30  
 79427 Eschbach  
 Phone +49 7634 5057-0  
 Fax +49 7634 5057-99  
 info@pimicos.com  
 www.pi.ws

**PI Ceramic GmbH**  
 Lindenstrasse  
 07589 Lederhose  
 Phone +49 36604 882-0  
 Fax +49 36604 882-4109  
 info@piceramic.com  
 www.piceramic.com



© Physik Instrumente (PI) GmbH & Co. KG  
 All contents, including texts, graphics, data etc., as well as their layout, are subject to copyright and other protective laws. Any copying, modification or redistribution in whole or in parts is subject to a written permission of PI.

Although the information in this document has been compiled with the greatest care, errors cannot be ruled out completely. Therefore, we cannot guarantee for the information being complete, correct and up to date. Illustrations may differ from the original and are not binding. PI reserves the right to supplement or change the information provided without prior notice.

Follow us on:  

## Subsidiaries

### USA (East) & CANADA

**PI (Physik Instrumente) L.P.**  
 Auburn, MA 01501  
 www.pi-usa.us

### USA (San Francisco Bay Area)

**PI (Physik Instrumente) L.P.**  
 Sausalito, CA 94965  
 www.pi-usa.us

### ITALY

**Physik Instrumente (PI) S. r. l.**  
 Bresso  
 www.pionline.it

### FRANCE

**PI France SAS**  
 Aix-en-Provence  
 www.pi.ws

### JAPAN

**PI Japan Co., Ltd.**  
 Tokyo  
 www.pi-japan.jp

### CHINA

**Physik Instrumente (PI Shanghai) Co., Ltd.**  
 Shanghai  
 www.pi-china.cn

### SOUTHEAST ASIA

**PI (Physik Instrumente) Singapore LLP**  
 Singapore  
 www.pi-singapore.sg  
 For ID / MY / PH / SG / TH / VNM

### KOREA

**PI Korea Ltd.**  
 Seoul  
 www.pikorea.co.kr

### USA (West) & MEXICO

**PI (Physik Instrumente) L.P.**  
 Irvine, CA 92620  
 www.pi-usa.us

### UK & IRELAND

**PI (Physik Instrumente) Ltd.**  
 Cranfield, Bedford  
 www.physikinstrumente.co.uk

### NETHERLANDS

**PI Benelux B.V.**  
 Sint-Oedenrode  
 www.pi.ws/benelux

### SPAIN

**Micos Iberia S.L.**  
 Vilanova i la Geltrú  
 www.pimicos.es

**PI Japan Co., Ltd.**  
 Osaka  
 www.pi-japan.jp

**Physik Instrumente (PI Shanghai) Co., Ltd.**  
 Beijing  
 www.pi-china.cn

### TAIWAN

**Physik Instrumente (PI) Taiwan Ltd.**  
 Taipei  
 www.pi-taiwan.com.tw